Professor Alberto M. Cuitiño
American Academy of Mechanics
School of Engineering
Rutgers University
98 Brett Road
Piscataway, NJ 08854-8058

Non-profit Organization
U.S. Postage
P A I D
New Brunswick, NJ
Permit No 157

mechanics

Academia Americana de Mecánica ● American Academy of Mechanics

Volume 35, Number 9-10 **September-October 2006**

ADVERTISEMENT POLICY

An advertisement for a position opening is charged a flat rate of $200. Payment must be done by check to the order of American Academy of Mechanics or credit card (Visa and MasterCard only) and sent to: American Academy of Mechanics, Alberto M. Cuitiño, School of Engineering, Rutgers University, 98 Brett Road, Piscataway, NJ 08854-8058. E-mail: **mechanics@soemail.rutgers.edu.**

The FID number for AAM is 23-7045163. Announcements for forthcoming events, conferences, and workshops are free of charge. Advertisements may be sent by FAX or e-mail (MSWord, PDF or plain text). Logo of the institution may be included if the graphic file is provided.

Mechanics is a bi-monthly magazine. To be considered for publication in forthcoming issues, an advertisement must be received one month in advance of the publication date. For example, an advertisement must be received before the end of November to appear in the January-February issue. Please note that the magazine is distributed near the end of the two-month period. The advertisement will continue to appear in future issues until the deadline of the position opening.

Visit the AAM website to read recent advertisements of position openings and past issues of Mechanics at **www.AAMech.org**.

mechanics

mechanics provides its readers with news in the field of theoretical and applied mechanics, and serves as a forum for the presentation and discussion of issues related to the development of the science and profession of mechanics. Opinions expressed are those of the authors and do not necessarily reflect official points of views of AAM or the institutions with which the authors are affiliated.

The American Academy of Mechanics is a non-profit corporation incorporated in 1969 under the laws of the Commonwealth of Pennsylvania. Its objective is to advance the science and profession of mechanics, with particular reference to the countries of North, South, and Central America. It aims to facilitate cooperation among mechanicists, to encourage recognition of achievements in mechanics, and to promote public understanding of the work of the mechanicist.

mechanics (ISSN 0076-5783) **POSTMASTER**: Send address changes to *mechanics*, Subscription and Membership, ESM, MC 0219, Virginia Tech, Blacksburg, VA 24061 (Tel. 540-231-6871: Fax 540-231-2290). Editorial and Advertising: Alberto M. Cuitiño, Rutgers University, 98 Brett Rd., Piscataway, NJ 08854-8058 (Tel. 732-445-4210, Fax 732-445-3124). Membership in the American Academy of Mechanics includes the subscription to *mechanics*.

American Academy of Mechanics
Academia Americana de Mecánica

SOCIETY ANNOUNCEMENT

The American Academy of Mechanics is pleased to announce the awardees for the Founder's Prize and Grant for 2006-2007. These are Mr. Vijay Shilpiekandula of the Massachhusetts Institute of Technology, for his essay "Progress Through Mechanics: Small-Scale Gaps" and Mr. Patrick Dondl of the California Institute of Technology, for his essay "Progress Through Mechanics: The Martensitic Phase Transformation." These essays will be reprinted in "mechanics," beginning this installment with Mr. Shilpiekandula's essay, and concluding in the next issue with Mr. Dondl's work. These essays will also be made available in the Founder's Prize and Grant section of the American Academy of Mechanics website, http://www.aamech.org/prize.html.

Progress through Mechanics: Small-scale Gaps

Vijay Shilpiekandula
Ph.D. Candidate, Department of Mechanical Engineering
Massachusetts Institute of Technology, Cambridge, MA 02139, USA
Phone: 617-258-6784; Email: svijay@mit.edu

In his 1959 talk titled, "There's plenty of room at the bottom," Nobel Laureate Professor Richard Feynman predicted that innovations that allow for "manipulating and controlling things on a small-scale" should be possible [1]. Advances in manufacturing have triggered many instances of such innovations, and promise to provide more opportunities for exploring length scales from a micrometer (μm) down to a nanometer (nm). Miniaturization of originally large-scale technologies to the size of a credit card, or even a single chip, has made mass-production at low costs feasible [2, 3]. While efforts are being channeled in this direction, there remains a critical need for precision tools that can advance an understanding of the fundamental science at small-scales, and, in turn, can accelerate the progress towards mass-production.

Small-scale gaps with sizes in the nm-μm range are leading examples of such precision tools. This range corresponds to the length scales of common particles such as biological macromolecules, cells, and metallic nanoparticles. For instance, our red blood cells are about 10 μm in size. Gold and silver nanoparticles causing exquisite colors in stained glass windows, such as the rose window of the Notre Dame Cathedral in Paris, have sizes on the order of 10-100 nm [4]. Gaps with sizes comparable to such common particles are ideal for manipulating and controlling them, and also for characterizing fields, forces and flows at small-scales.

Small-scale gaps have been fabricated using either bottom-up or top-down approaches for numerous applications [5]-[11]. Bottom-up approaches build devices molecule by molecule to generate the desired structure. A protein containing a nanometer-scale gap, and self-assembled into a lipid bi-layer membrane, was used for detecting DNA by monitoring the ionic conductance of the gap in [7]. Top-down approaches are based on reducing dimensions from large to small, and typically involve advanced fabrication techniques. A 91 nm gap formed between metal electrodes was used for measuring the dielectric properties of single molecules as a function of frequency in [9]. A 35 nm gap formed between polysilicon electrodes was used as part of a fluidic transistor that controls the flow of ions in [11].

Programmability is a key feature absent in the gaps mentioned above. A gap that can be programmed to a desired size can be useful for a wider range of applications. A promising method to achieve such programmable gaps involves a precision variation of the separation between two optically flat surfaces held parallel to each other [12]. Existing designs [13]-[16] provide many choices, including atomically smooth mica films and fused silica plates, for forming such gaps. However, these designs do not address the critical features of (i) maintaining precise parallelism between the flat surfaces to ensure gap uniformity and (ii) robust gap control in the presence of uncertainties [17, 18] at small-scales. The following applications are uniquely enabled by a uniform and robustly programmable small-scale gap:

1. Rapid DNA Pattern Replication: A novel stamping technique proposed in [19] allows for duplicating a DNA pattern from a master to a secondary substrate. This technique can be applied to DNA microarrays, potentially reducing their unit cost from the current value of $500 to $50. The low cost can make DNA analysis a routine procedure for early diagnosis of diseases such as Alzheimer's, AIDS, and liver cancer [20]. However, the promise of this technique cannot be realized until the "stamping step" is optimized. This step involves maintaining a uniform gap on the order of 10 nm between the substrates to enable pattern transfer. A robust parallel-plate construct maintaining a nanometer-scale gap is directly applicable to this problem. Further, dynamic characterization of DNA binding events can enable understanding the replication kinetics.

2. Size-based Filtrations: Porous membranes are used in biotechnology and pharmaceutical industries to sieve biological macromolecules such as proteins and nucleic acids [21]. However, size-selectivity of such membranes is limited by the distribution of pore sizes about a nominal value [22]. A robust small-scale gap can mimic a pore having a controlled size. An atomic-scale resolution for the variation of the gap can ensure high size-selectivity for the sieving of nanoparticles [23]. A parallel combination of many gaps can enable faster separations, and can be part of high-throughput automated systems used for diagnostics, drug discovery, and genomic and proteomic analyses [24, 25].

3. Characterization of Near-field Physics: A robust small-scale gap formed between parallel plates can be used to experimentally characterize near-field physical phenomena at various gap sizes in the nm-μm range. Example phenomena include radiative heat transfer and quantum-dynamic forces, such as Casimir forces [26]. Near-field radiative heat transfer has applications in thermophotovoltaics [27], an area that focuses on generating electricity from infrared radiation [28]. Understanding Casimir forces is essential from the standpoint of a related phenomenon called stiction, which adversely affects the fabrication of most MEMS devices [29].

4. Non-conventional Lithography: Feature resolutions possible with industrial lithography based on optical projection are diffraction-limited. Non-conventional techniques such as (i) contact, (ii) plasmon, and (iii) nano-imprint lithographies can generate much smaller features. In such techniques, a robust and uniform nanometer-scale gap, or contact (zero gap), needs to be maintained between the mask and the wafer.

In summary, programmable small-scale gaps formed between optically flat surfaces are an enabling technology for many promising applications, some of which are envisioned above. To form such gaps, an integrated approach based on mechanics is necessary. Such an approach should take into account not only the design, but also modeling and control [30]. Any effort

involving the design, fabrication, and practical use of small-scale gaps should be initiated by inter-disciplinary teams composed of personnel with diverse skill sets. The inter-disciplinary work can bring fresh perspectives, and catalyze novel approaches to challenging problems. Such meaningful work can potentially groom into long-term collaborations that make impactful contributions to diverse fields, such as genomic and proteomic analyses, medical diagnostics, lithography, energy, and micro/nano systems. The extent of possibilities can only be left to one's imagination because there surely seems to be, as Professor Feynman [1] believed, "plenty of room at the bottom."

Acknowledgements

The author would like to thank Professors Kamal Youcef-Toumi and Stephen Crandall for their guidance and support, and the collaborators in this work: research groups of Professors Gang Chen, Francesco Stellacci, and Karl Berggren of MIT for discussing their applications.

References

[1] Feynman RP, "There's plenty of room at the bottom," *Engineering and Science,* vol. 23, pp. 22-36, Feb 1960. Talk delivered at California Institute of Technology, Pasadena, CA, USA, December 29, 1959. Online version of transcript available via URL: http://www.zyvex.com/nanotech/feynman.html, URL last accessed: Jun 2006.

[2] Mitchell P, "Microfluidics - downsizing large-scale biology," *Nature Biotechnology,* vol. 19 (8), pp. 717-721, Aug 2001.

[3] Sauer S, Lange BMH, Gobom J, et al, "Miniaturization in Functional Genomics and Proteomics," *Nature Reviews Genetics,* vol. 6 (6), pp. 465-476, Jun 2005.

[4] Haes AJ, Stuart DA, Nie SM, et al, "Using solution-phase nanoparticles, surface-confined nanoparticle arrays and single nanoparticles as biological sensing platforms," *Journal of Fluorescence,* vol. 14 (4), pp. 355-367, Jul 2004.

[5] Lefebvre J, Radosavljevic M, and Johnson AT, "Fabrication of nanometer size gaps in a metallic wire source," *Applied Physics Letters,* vol. 76 (25), pp. 3828-3830, Jun 2000.

[6] Choi J, Lee K, and Janes DB, "Nanometer scale gap made by conventional microscale fabrication: step junction," *Nano Letters,* vol. 4 (9), pp. 1699-1703, Sep 2004.

[7] Wang H and Branton D, "Nanopores with a spark for single-molecule detection," *Nature Biotechnology,* vol. 19, pp. 622-623, 2001.

[8] Reed MA, Zhou C, Muller CJ, et al, "Conductance of a molecular junction," *Science*, vol. 278 (5336), pp. 252-254, Oct 1997.

[9] Ionescu-Zanetti C, Nevill JT, Di Carlo D, et al, "Nanogap capacitors: sensitivity to sample permittivity changes," *Journal of Applied Physics,* vol. 99 (2), Art. No. 024305, Jan 2006.

[10] Liang WJ, Shores MP, Bockrath M, et al, "Kondo resonance in a single-molecule transistor," *Nature*, vol. 417 (6890), pp. 725-729, Jun 2002.

[11] Karnik R, Fan R, Yue M, et al, "Electrostatic control of ions and molecules in nanofluidic transistors," *Nano Letters,* vol. 5, pp. 943-948, May 2005.

[12] Slocum AH, "Method of and apparatus for substance processing with small opening gates actuated and controlled by large displacement members having fine surface finishing," US Patent # 596442, 1999.

[13] Peachey J, Vanalsten J, and Granick S, "Design of an apparatus to measure the shear response of ultrathin liquid-Films," *Review of Scientific Instruments,* vol. 62 (2), pp. 463-473, Feb 1991.

[14] More T, Dax C, Niemela J, et al, “A new low temperature device for high resolution, in situ measurement and control of submicron gaps,” *Journal of Low Temperature Physics,* vol. 121 (5-6), pp. 825-830, Dec 2000.
[15] White JR, “The Nanogate: nanoscale flow control,” Ph.D. Thesis. Department of Mechanical Engineering, Massachusetts Institute of Technology, Cambridge MA 02139, USA, Jun 2003; White JR, Ma H, Lang J, and Slocum AH, “An instrument to control parallel plate separation for nanoscale flow control," *Review of Scientific Instruments*, vol. 74 (11), pp. 4869-4875, Nov 2003; Ma H, White J, Paradiso J, and Slocum AH, “Sub-nanometer displacement sensing for the Nanogate - a tunable nanometer Gap," In Proceedings of *IEEE Sensors*, vol. 1 (22-24), pp. 46-51, Oct 2003; White JR, White CJ, and Slocum AH, “Octave-tunable miniature RF resonators," *IEEE Microwave and Wireless Components Letters,* vol. 15 (11), pp. 793-795, Nov. 2005.
[16] Chakraborty I, Tang WC, Bame DP, and Tang TK, “MEMS micro-valve for space applications,” *Sensors and Actuators,* vol. 83, pp. 188-193, May 2000.
[17] Sebastian A and Salapaka SM, “Design methodologies for robust nano-positioning,” *IEEE Transactions on Control Systems Technology,* vol. 13 (6), pp. 868-876, Nov 2005.
[18] El Rifai OM and Youcef-Toumi K, “Adaptive control of uncertain dynamics at the nanoscale,” *44th IEEE Conference on Decision and Control, 2005 and 2005 European Control Conference,* pp. 1180-1184, Dec 2005.
[19] Yu AA, Savas TA, Taylor GS, et al, “Supramolecular nanostamping: Using DNA as movable type,” *Nano Letters,* vol. 5 (6), pp. 1061-1064, Jun 2005.
[20] Clark L, “New technique may speed DNA analysis,” *MIT Tech Talk,* May 18, 2005, Online version of text available via URL http://web.mit.edu/newsoffice/2005/techtalk49-28.pdf, URL last accessed: Jun 2006.
[21] Ogston AG, *Transactions of the Faraday Society*, vol. 54, pp. 1754-1757, 1958.
[22] Akthakul A, Hochbaum AI, Stellacci F, and Mayes AM, “Size fractionation of metal nanoparticles by membrane filtration," *Advanced Materials,* vol. 17 (5), pp. 532-535, Mar 2005.
[23] Shilpiekandula V and Youcef-Toumi K, “Modeling and control of a programmable filter for separation of biologically active molecules," In Proceedings of the *American Control Conference,* pp. 394 - 399, Jun 2005.
[24] Issaq HJ, “The role of separation science in proteomics research,” *Electrophoresis,* vol. 22 (17), pp. 3629-3638, Oct 2001.
[25] Chou CF, Austin RH, Bakajin O, et al, “Sorting biomolecules with microdevices,” *Electrophoresis,* vol. 21 (1), pp. 81-90, Jan 2000.
[26] Joulain K, Mulet JP, Marquier F, et al, “Surface electromagnetic waves thermally excited: Radiative heat transfer, coherence properties and Casimir forces revisited in the near-field,” *Surface Science Reports*, vol. 57 (3-4), pp. 59-112, May 2005.
[27] Narayanaswamy A and Chen G, “Surface modes for near-field thermophotovoltaics," *Applied Physics Letters,* vol. 82 (20), pp. 3544-3546, May 19, 2003.
[28] Coutts TJ, “An overview of thermophotovoltaic generation of electricity,” *Solar Energy Materials and Solar Cells,* vol. 66 (1-4), pp. 443-452, Feb 2001.
[29] Serry FM, Walliser D, and Maclay GJ, “The anharmonic Casimir oscillator - the Casimir effect in a model microelectromechanical system,” *Journal of Microelectromechanical Systems,* vol. 4 (4), pp. 193-205, Dec 1995.
[30] Youcef-Toumi K, “Modeling, design, and control integration: a necessary step in mechatronics,” *IEEE/ASME Transactions on Mechatronics,* vol. 1 (1), pp. 29-38, Mar 1996.

POSITION AVAILABLE

Cornell University
School of Civil and
Environmental Engineering

Announces two tenure-track faculty positions in structural engineering starting in Fall 2007-2008. At Cornell, structural engineering is conceived of broadly. Thus we are seeking candidates with a passion for applying fundamental principles of physics, cast within the framework of solid and structural mechanics, to enable improvements in understanding and design of complex structural systems in a multi-scale context, and across a range of materials.

In this spirit, two complementary candidates are sought:

1) *High performance materials. Position #00127814* - The successful candidate for position one is expected to advance the analysis and design of structural systems made of high-performance materials including concrete structures by integrating structural mechanics with multi-scale modeling and advanced experimentation**.** The Cornell NEES site and the newly renovated Bovay Laboratory Complex will likely be of value to this candidate's research program.
2) *Computational mechanics. Position #00141783* - The successful candidate for position two is expected to have expertise in multi-scale modeling and simulation of materials and structures with considerable background and interest in uncertainty quantification. The cyber infrastructure capabilities of the Cornell Theory Center will likely be of value to this candidate's research program.

For both positions, additional supporting interests and expertise in areas such as smart and multifunctional materials, earthquake engineering, risk and reliability, and sensing and structural health monitoring will be considered. Additional information may be found at http://www.cee.cornell.edu/

The successful candidates for these positions will seek innovative solution methodologies to challenging structures problems wherever they may be. Candidates must have a PhD in engineering or an allied field within the physical sciences.

Appointments at the rank of Assistant Professor are anticipated, but applications from candidates from all levels are welcomed. Applications will be held in strict confidence. To apply please mail a detailed resume, statement of professional research and teaching goals, official graduate transcript, and the names, addresses, e-mail addresses, and phone and fax numbers of at least three references to:

Structural Engineering Search Committee Chair
School of Civil and Environmental Engineering
220 Hollister Hall, Cornell University, Ithaca, New York 14853-3501

In addition, electronic copies of all application materials must be submitted on-line at http://www.cee.cornell.edu/position_search/ Review of applications will begin immediately and continue until the position is filled.

The College of Engineering is an equal-opportunity, affirmative-action employer committed to employing a highly qualified, diverse faculty. Women and minorities are encouraged to apply for these positions.

APPLICATION FOR MEMBERSHIP

Academia Americana de Mecánica • **American Academy of Mechanics**

Preferred title and full name (please print):

_____

Send mail to: [ ] office [ ] residence (please include both)

Office Address: Residence Address:

_____ _____

_____ _____

_____ _____

Daytime telephone / Fax number / EMAIL address (please note if not used)

_____/_____/_____

I hereby apply to be admitted as a Member of the *American Academy of Mechanics (AAM).*

I enclose a copy of my **curriculum vitae**, and I believe that the work indicated herein qualifies me for membership in the *AAM* in conformity with the requirements of Article II of the Bylaws concerning membership.

I enclose the **current fees** as indicated on the following Membership Fees Schedule.

Signature_____ Date _____

Membership Fees Schedule* (Membership includes a subscription to **mechanics**)
(Please check the amount enclosed)

Professional Members	**Student Members**	**Organization Subscription**	**Retired**
[ ] North America $52	[ ] North America $30	[ ] Worldwide $100	[ ] Worldwide $15
[ ] Latin America $30	[ ] Latin America $15		
[ ] All others $52	[ ] All others $30		

_____ / _____ _____ _____

Visa [ ] MasterCard [ ] No. Exp. Date Owner of Credit Card (Please Print) Signature

Please mail your (1) **completed application**, (2) **curriculum vitae**, and (3) **fee payment** (please make checks payable to **American Academy of Mechanics**) to:

American Academy of Mechanics
ATTN: Liz Montana
Department of Mechanical Engineering
University of California
Santa Barbara, CA 93106

For questions or assistance:
805-893-4459 · · Fax**: 805-893-4985** · · email: **liz@engineering.ucsb.edu** · · · **http://www.aamech.org/**

*All Members may pay by either credit card or check, if the check is written in US$ on a US bank. We have had problems with currency exchange. If you cannot pay in US$ on a US bank, then please pay by credit card.